


R SERIES WORM SPEED REDUCE

NMRV Series worm speed reducer is an INDIAN PRODUCT developed indigenously and manufactured according to the International Standard.


| | |
|-----------------|------------------------|
| Center Distance | : upto 150 mm |
| Ratio | : 7.5:1 - 100 : 1 |
| Torque | : upto 250 Kgm |
| Input Power | : 0.16 HP - 7.5 HP |
| Mounting | : Universal mounting |
| Output Shaft | : Hollow 14 mm - 50 mm |



WORM SPEED REDUCE

NMRV Series worm speed reducer is an INDIAN PRODUCT developed indigenously and manufactured according to the International Standard.

| | |
|-----------------|------------------------|
| Center Distance | : upto 150 mm |
| Ratio | : 7.5:1 - 100 : 1 |
| Torque | : upto 250 Kgm |
| Input Power | : 0.16 HP - 7.5 HP |
| Mounting | : Universal mounting |
| Output Shaft | : Hollow 14 mm - 50 mm |



DOUBLE WORM SPEED REDUCER

NMRV Series worm speed reducer is an INDIAN PRODUCT developed indigenously and manufactured according to the International Standard.

| | |
|-----------------|------------------------|
| Center Distance | : upto 150 mm |
| Ratio | : 100:1 - 5000 : 1 |
| Torque | : upto 250 Kgm |
| Input Power | : 0.16 HP - 7.5 HP |
| Mounting | : Universal mounting |
| Output Shaft | : Hollow 14 mm - 50 mm |



PLANETARY DRIVE

Compact, Study, multiple planet meshing allows power transmission through several path yet extremely powerful high torque transmission & ultimately smaller design, make ideal for sever duty application where shocks & impact are more...

| | |
|---------------------|--|
| Ratio | : 3.26 Onwards |
| Torque | : 25000 KGM |
| Input Power | : Electric Motor 0.25 HP - 150 HP Hydraulic Moor, Servo Motor |
| Mounting | : Foot Flange Agitator and Special Mounting |
| Output Shaft | : Solid / Hollow Shaft, Solid Hollow Spline Shaft, Shrink Disk with Torque Arm |
| Right Angle Version | : Worm Planetary, Bevel Planetary |



A.C. ELECTRIC MOTORS

Harmonic make electric motor comes with high efficiency and longer life. Using the standards 12615:2018, we are now one of the leading brand in this product. We are also providing the customized motors with varieties in duties (S1 to S4) & as per specifications and applications.

| | |
|-------------|---|
| Input Power | : 0.25 HP to 30.0 HP |
| RPM | : 720, 960, 1440, 2880 |
| Voltages | : 220, 380, 415, 440 |
| Frequency | : 50 Hz, 60 Hz |
| Mounting | : Foot mounted (B3), Flange mounted (B5), Face vertical (B14) |



SMALL GEARED MOTOR

We have introduced new series of small watt geared motor from 25 Watts - 360 Watts and with various gear ratios. Small geared motors are of 3 phase, 1 phase which are adoptable for the gearboxes.

| | |
|---------------|------------------------|
| Power AC / DC | : 25 Watts - 250 Watts |
| Ratio | : 3 : 1 - 300 : 1 |
| Mounting | : Foot / flange type |



HELICAL GEAR MOTOR

Dependable, high performance, compact, study & Cast iron housing, Low noise and smooth working, long trouble-free operation.

| | |
|-------------|---------------------------------------|
| Ratio | : 5:1 to 200:1 |
| Input Power | : Electric Motor - 0.25 HP to 12.5 HP |
| | : Free Input |
| Torque | : upto 20000 kgm |
| Mounting | : Foot / Flange |



BLOWERS

Introducing the First time in India, the vacuum blower series manufacturing plant. What you have expected from others you will get it here, a Powerfull and the energy-saving range of the blower are suitable for all the suck and throw applications.

| | |
|----------------------|--------------------------|
| Power | : 0.25 kW to 7.5 kW |
| Voltage | : 360 to 415, 230 +- 10% |
| Phase | : 3 Phase and 1 Phase |
| R.A.M. | : 2880 |
| Frequency | : 50 Hz, 60 Hz |
| Degree of Protection | : IP 54 |
| Insulation class | : F class |

[®]
PIZEN
QUALITY YOU DESIRE

UDAY ENGITECH

3, Bhagvati Estate, Nr. Keval Kanta, Rakhial, Ahmedabad - 380023.

Email : udayengitech@gmail.com

Office : 09909010442

Mob. : 08238156566 | 09687676312